

DUMPSQUEEN

HCIA-LTE-RNP&RNO V1.0

Huawei H35-560

Version Demo

Total Demo Questions: 10

Total Premium Questions: 84

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

Which physical channel in LTE is used to carry paging messages?

- A. PBCH
- B. PDSCH
- C. PDCCH
- D. PUCCH

ANSWER: B

QUESTION NO: 2

In the downlink scheduling, which factors will affect the allocation of downlink shared resources and the selection of MCS?
(Multiple Choice)

- A. UE capability level
- B. The wireless environment where the user is located
- C. Cache status
- D. PHR (power headroom report) of UE

ANSWER: A B

QUESTION NO: 3

The insertion loss of the cavity power divider is larger than that of the microstrip power divider.

- A. True
- B. False

ANSWER: B

QUESTION NO: 4

Which of the following information can be observed directly through the Probe drive test tool? (Multiple choice)

- A. PUSCH, PUCCH, RACH, and sRS physical channel transmit powercorrect
- B. TM modecorrect
- C. Number of occupied carrierscorrect
- D. UE real-time transmit power

ANSWER: A B C

QUESTION NO: 5

Before the cluster optimization test, the target area must be divided into clusters. Which of the following statements are correct? (Multiple choice)

- A. The cluster division should span different areas of the test (planning) full coverage business
- B. Make full use of the terrain (mountains and rivers)
- C. Refer to the existing cluster division for network engineering maintenance
- D. When dividing the cluster, the drive test in each cluster can be completed in one day, usually about 6 hours for one drive test

ANSWER: B C

QUESTION NO: 6

In the case of FTP download or upload (or packet filling) without manual intervention, the throughput rate should be maintained at this time. If there is a sudden drop, call drops may occur.

- A. True
- B. False

ANSWER: A

QUESTION NO: 7

ASSTANT is a front-end test tool independently developed by Huawei, which can display test data, replay test data, and export test data.

- A. True
- B. False

ANSWER: B

QUESTION NO: 8

Which of the following adjustment measures has the highest priority?

- A. Antenna height
- B. Antenna direction angle antenna downtilt angle
- C. Antenna type

ANSWER: C

QUESTION NO: 9

Which of the following is the correct description of the following LTE neighboring cell planning? (Multiple choice)

- A. Geographically directly related Neighboring cells are generally used as neighboring cells
- B. For dense urban areas and ordinary urban areas, the distance between stations is relatively close (0.3-1.0kilometer),Neighborhood should do more
- C. becauseforLTEofThe neighboring area does not exist in orderI,CanProblem, and the detection cycle is very short, so you only need to consider not missing neighbors, not wantSort neighboring cells strictly according to signal strength
- D. ANRThe function can completely replace the initial networkNeighbourhood planning

ANSWER: A B C

QUESTION NO: 10

During the X2 handover in the LTE system, if re-establishment occurs, which cells may be re-established? (Multiple choice)

- A. Source area

- B. ItemTarget area
- C. Third-party community
- D. Other cells in the source base station

ANSWER: A B D