

DUMPSQUEEN

HCNP - LTE RNP & RNO

Huawei H35-561

Version Demo

Total Demo Questions: 10

Total Premium Questions: 60

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

Which of the following options are steps in the DCI encoding process? (multiple choice)

- A. Information unit multiplexing
- B. CRC addition
- C. Channel coding
- D. Rate matching
- E. Code block cascade

ANSWER: A B C D

QUESTION NO: 2

Both LTE uplink and downlink use SC-FDMA technology.

- A. True
- B. False

ANSWER: B

QUESTION NO: 3

Probe is an air interface test tool, mainly used to collect LTE network air interface test data.

- A. True
- B. False

ANSWER: A

QUESTION NO: 4

Antenna feed adjustment refers to the adjustment of antenna azimuth and downtilt angle. The most commonly used method is to eliminate cross-area coverage, weak coverage, and PCI mode 3 conflicting cells.

- A. True
- B. False

ANSWER: A

QUESTION NO: 5

How many codewords can be transmitted at most for a TT in the LTE system?

- A. 1
- B. 2
- C. 3
- D. 4

ANSWER: B

QUESTION NO: 6

Which of the following are NAS EMM? (multiple choice)

- A. Attach
- B. Tracking area update
- C. Authentication
- D. EPS bearer setup

ANSWER: A B C

QUESTION NO: 7

The path loss value obtained from the link budget is the median value. The actual path loss fluctuates within this value. In order to ensure a certain edge coverage probability (such as >75%), a certain margin needs to be left. This margin is mainly related to the radio wave. Which of the following characteristics of propagation are irrelevant? (multiple choice)

- A. Frequency selectivity

- B. Fast fading
- C. Depolarization
- D. Shadow fading

ANSWER: A B C

QUESTION NO: 8

What are the statistics of the switch analysis report output? (multiple choice)

- A. Switching times
- B. Number of successful switching
- C. Switching failure times
- D. Handover success rate

ANSWER: A B C D

QUESTION NO: 9

What are the types of switching according to the trigger reason? (multiple choice)

- A. Overlay-based handover
- B. Load-based handover
- C. Business-based handover
- D. Handover based on UE moving speed

ANSWER: A B C D

QUESTION NO: 10

Which of the following KPI indicators belong to the retention category?

- A. Paging success rate
- B. RRC connection establishment success rate

C. Drop rate

D. Resource block utilization

ANSWER: C