

DUMPSQUEEN

Certified Wireless Specialist

CWNP CWS-100

Version Demo

Total Demo Questions: 10

Total Premium Questions: 60

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

What common vendor feature can be enabled to encourage client devices to use a 5 GHz connection instead of a 2.4 GHz connection?

- A. Dynamic Frequency Selection (DFS)
- B. Dynamic Rate Switching (DRS)
- C. Band Steering
- D. Fast BSS Transition (FT)

ANSWER: C

QUESTION NO: 2

When planning for a bridge link between locations, in addition to the link distance, what requirement should be known in order to determine the antennas, settings and bridges to use?

- A. Required color
- B. Required power sourcing method
- C. Required throughput
- D. Required cable length

ANSWER: B

QUESTION NO: 3

What network service is used to provide automatic Internet Protocol configuration for network client devices?

- A. DNS
- B. DHCP
- C. ARP
- D. NTP

ANSWER: B

QUESTION NO: 4

For what is the S1G (Sub-1 GHz) PHY (Physical Layer) most likely to be used?

- A. Tablets
- B. IoT (Internet of Things)
- C. Laptops
- D. Desktops

ANSWER: B

QUESTION NO: 5

What is the maximum latency or delay requirement in milliseconds for many voice over IP (VoIP) devices?

- A. 150 ms
- B. 100 ms
- C. 50 ms
- D. 20 ms

ANSWER: A

QUESTION NO: 6

Which one of the following is an example of a multi-band device?

- A. A laptop supporting only 802.11n in 2.4 GHz
- B. A laptop supporting 802.11n, 802.11ac, and 802.11ad
- C. A laptop supporting only 802.11n in 5GHz
- D. A laptop supporting only 802.11a

ANSWER: B

QUESTION NO: 7

In a highly-reflective environment, what result can have a negative impact on SISO 802.11 devices?

- A. Increased signal strength
- B. Multipath
- C. Phase shifts
- D. Increased bits in the signal

ANSWER: B

QUESTION NO: 8

What 802.11 fast roaming solution allows a client to authenticate to a different AP than that to which it is connected through the AP to which it is connected?

- A. Role-Based Access Control (RBAC)
- B. Preauthentication
- C. Captive Portal
- D. Virtual Private Network (VPN)

ANSWER: B

QUESTION NO: 9

When open public Wi-Fi access is provided, what can be implemented to help prevent attacks between devices connected to the same AP?

- A. WPA2
- B. WPA
- C. Device-to-device communication blocking
- D. WEP

ANSWER: C

QUESTION NO: 10

What channel width rarely, if ever, should be used in the 2.4 GHz frequency band, even though it is supported by the standard and available devices?

- A. 160 MHz

B. 20 MHz

C. 22 MHz

D. 40 MHz

ANSWER: A