

DUMPSQUEEN

Extreme Networks Specialist

Extreme Networks EW0-300

Version Demo

Total Demo Questions: 10

Total Premium Questions: 158

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

An Ethernet Automatic Protection Switching (EAPS) domain relies on a control VLAN. That control VLAN must be tagged with an 802.1Q tag.

- A. TRUE
- B. FALSE

ANSWER: A

QUESTION NO: 2 - (SIMULATION)

SIMULATION

What is the Area ID of the only pre-configured OSPF area in all Extreme Switches?

ANSWER: 0.0.0.0

QUESTION NO: 3

The following modes of operation are supported with the Network login feature. (choose all that apply)

- A. Secure mode
- B. Campus mode
- C. Quick Mode
- D. ISP mode

ANSWER: A B C D

QUESTION NO: 4

Traffic involved with Policy based QoS is handled by the switch its CPU.

- A. True
- B. False

ANSWER: B

QUESTION NO: 5

In SLB the forwarding mode is the method a switch uses to forward traffic to the virtual servers. On the Summit 7i switch four forwarding modes are supported, select the two forwarding modes that are hardware based.

- A. Transparent mode
- B. Translation mode
- C. Port Translation mode
- D. GoGo mode

ANSWER: A B C D

QUESTION NO: 6

ESRP-enabled switches can utilize either an IP address or an IPX net ID for their protected VLANs.

- A. TRUE
- B. FALSE

ANSWER: A

QUESTION NO: 7

What is the RP-set?

- A. It is the information of which RP are available for what Multicast groups. It is send by the BSR towards all PIM routers
- B. It is the information of which multicast groups are active It is send by the RP towards all PIM routers
- C. It is the information of which BSR are available for what Multicast groups. It is send by RP towards all PIM routers
- D. It is the information, stored by all RP, needed to find the BSR.

ANSWER: A

QUESTION NO: 8

The following ExtremeWare components are required on Extreme Networks switches with the '1' series chipset to build an SLB system. (Choose all three that apply)

- A. Nodes
- B. Pools
- C. Virtual Servers
- D. Load balance cache engines

ANSWER: A B C

QUESTION NO: 9

When SSH2 is configured and enabled on a Summit 7i switch, telnet is automatically disabled.

- A. True
- B. False

ANSWER: B

QUESTION NO: 10

What mechanisms does a master node use to detect a failure in the EAPS ring architecture? Select the two that apply.

- A. The master node receives a trap-message from a transit node when it detects loss of link connectivity on any of its ring ports.
- B. The master node uses OSPF to quickly learn about link state topology changes.
- C. The master node sends a health-check packet on the control VLAN, when the ring breaks the master node stops receiving this packet on its secondary port.
- D. The master node uses IGMP and IGMP snooping to detect the transit nodes and than to learn about failures in the topology between them.

ANSWER: A C