

# DUMPSQUEEN

## Nuage Networks Virtualized Network Services (VNS) Fundamentals

Nokia 4A0-N02

Version Demo

Total Demo Questions: 5

Total Premium Questions: 40

Buy Premium PDF

<https://dumpsqueen.com>

[support@dumpsqueen.com](mailto:support@dumpsqueen.com)

dumpsqueen.com

## QUESTION NO: 1

Which of the following connections does not exist during the VNS bootstrapping process?

- A. Proxy to NSG
- B. Proxy to VSD
- C. NSG to VSC OpenFlow-TLS
- D. VSC to proxy

**ANSWER: D**

## QUESTION NO: 2

What type of NAT is used so that any external host can send to iAddr: iPort by sending traffic to eAddr: ePort? (i=internal, e=external)

- A. Full-cone NAT
- B. Address-restricted NAT
- C. Port-restricted NAT
- D. Symmetric NAT

**ANSWER: A**

## QUESTION NO: 3

Which of the following statements about the NSG support for NAT-T is TRUE?

- A. NAT-T is a network port level attribute.
- B. NAT-T NPM probes are disabled by default.
- C. Direct Symmetric to Symmetric mapping is supported.
- D. Address restricted mapping requires the use of two NPM probes.

**ANSWER: A**

## QUESTION NO: 4

Which of the following is NOT defined in the NSG infrastructure G/W profile?

- A. Identify the VSD proxy
- B. Enable two-factor installer authentication
- C. Port speed and mode
- D. NTP, stats, syslog server

**ANSWER: B**

## QUESTION NO: 5

Which of the following statements about the NSG vports is TRUE?

- A. The NSG responds to DHCP requests on a host vport by default.
- B. A host MAC address is dynamically learned on a host vport.
- C. A host vport allows multiple devices to be connected through a switch.
- D. IP address assignment is handled by the NSG for a host on a host vport.

**ANSWER: D**