Implementing Cisco SD-WAN Solutions (300-415 ENSDWI)

Cisco 300-415

Version Demo

Total Demo Questions: 15

Total Premium Questions: 314

Buy Premium PDF

https://dumpsqueen.com

support@dumpsqueen.com

dumpsqueen.com



Topic Break Down

Topic	No. of Questions		
Topic 1, New Update	129		
Topic 2, Architecture	34		
Topic 3, Controller Deployment	20		
Topic 4, Router Deployment	39		
Topic 5, Policies	35		
Topic 6, Security and Quality of Service	25		
Topic 7, Management and Operations	32		
Total	314		

QUESTION NO: 1

When software is upgraded on a vManage NMS, which two image-adding options store images in a local vManage software repository? (Choose two.)

- A. To be downloaded over an ICMP connection
- B. To be downloaded over a SNMP connection
- C. To be downloaded over a control plane connection
- **D.** To be downloaded over an out-of-band connection
- **E.** To be downloaded over a SMTP connection

ANSWER: C D

Explanation:

Reference: https://sdwan-

docs.cisco.com/Product Documentation/vManage Help/Release 18.2/Maintenance/Software Repository

QUESTION NO: 2

At which layer does the application-aware firewall block applications on a WAN Edge?

- **A.** 3
- **B**. 5
- **C**. 2
- **D**. 7

ANSWER: D

QUESTION NO: 3


A Cisco SD-WAN customer has a requirement to calculate the SHA value for files as they pass through the device to see the returned disposition and determine if the file is good, unknown, or malicious.

The customer also wants to perform real-time traffic analysis and generate alerts when threats are detected. Which two Cisco SD-WAN solutions meet the requirements? (Choose two.)

A. Cisco Threat Grid

B. Cisco Trust Anchor Module
C. Cisco AMP
D. Cisco Secure Endpoint
E. Cisco Snort IPS
ANSWER: A C
QUESTION NO: 4
Which Cisco SD-WAN component facilitates the initial communication between WAN Edge devices to join the fabric?
A. WAN Edge Router
B. vSmart Controller
C. vManage
D. vBond Orchestrator
ANSWER: D
QUESTION NO: 5
An engineer is adding a tenant with location ID 399533345 in vManage. What is the maximum number of alphanumeric characters that is accepted in the tenant name filed?
A . 64
B. 128
C. 256
D. 8
ANSWER: B
Explanation:
In the Add Tenant window:
a. Enter a name for the tenant. It can be up to 128 characters and can contain only alphanumeric characters.
QUESTION NO: 6

An administrator must deploy the controllers using the On-Prem method while vManage can access the PnP portal from inside. How are the two WAN Edge authorized allowed lists to be made available to vManage? (Choose two.)



A. Option A

- B. Option B
- C. Option C
- **D.** Option D
- E. Option E


ANSWER: A D

QUESTION NO: 7 - (DRAG DROP)


DRAG DROP

Drag and drop the policies from the left onto the correct policy types on the right.

Select and Place:



ANSWER:



Explanation:

QUESTION NO: 8

Which two products are used to deploy Cisco WAN Edge Router virtual platforms? (Choose two.)

- A. Sun Enterprise M4000 Server running Sun Solaris
- B. Sun SPARC Node running AIX
- C. Cisco UCS
- D. HP ProLiant DL380 Generation 10 running HP-UX
- E. Cisco ENCS 5000 Series

ANSWER: CE

Explanation:

Reference: https://www.cisco.com/c/en/us/products/collateral/routers/5400-enterprise-network-compute-system/datasheet-c78-738512.html


QUESTION NO: 9 - (DRAG DROP)

DRAG DROP

Drag and drop the components from the left onto the corresponding Cisco NFV Infrastructure Building Blocks on the right. Not all options are used.


Select and Place:

Answer Area



ANSWER:

Answer Area



Explanation:

QUESTION NO: 10

What are the two protocols redistributed into OMP? (Choose two.)

- A. OSPF
- B. RSVP
- C. LDP
- D. RIP
- E. EIGRP

ANSWER: A E

QUESTION NO: 11

Which TCP Optimization feature is used by WAN Edge to prevent unnecessary retransmissions and large initial TCP window sizes to maximize throughput and achieve a better quality?

- A. SEQ
- B. SYN
- C. RTT
- D. SACK

ANSWER: D

Explanation:

TCP Optimization

The Cisco SD-WAN TCP Optimization feature uses TCP Selective Acknowledgement (SACK) to prevent unnecessary retransmissions and large initial TCP window sizes in order to maximize throughput and achieve a better quality of experience.

QUESTION NO: 12

An enterprise has several sites with multiple VPNs that are isolated from each other A new requirement came where users in VPN 73 must be able to talk to users in VPN 50 Which configuration meets this requirement?

```
policy
  control-policy Route_Leaking
    sequence 1
    match route
     vpn-list VPN_73
     prefix-list _Anylpv4PrefixList
     action accept
     export-to vpn-list VPN_50
    sequence 11
    match route
     vpn-list VPN_50
     prefix-list_Anylpv4PrefixList
    action accept
     export-to vpn-list VPN 73
    default-action accept
  policy
  control-policy Route_Leaking
    sequence 1
    match route
     VPN_73
     prefix-list_Anylpv4PrefixList
     export-to VPN_50
    sequence 11
    match route
     VPN_50
     prefix-list_Anylpv4PrefixList
     export-to VPN_73
    default-action accept
```

- policy control-policy Route_Leaking sequence 1 match route VPN_ALL prefix-list_Anylpv4PrefixList action accept export-to VPN_ALL opolicy control-policy Route_Leaking sequence 1 match route VPN_50 VPN_73 prefix-list _Anylpv4PrefixList action accept export-to VPN_73 VPN_50
- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: A

QUESTION NO: 13

An engineer must apply the configuration for certificate installation to vBond Orchestrator and vSmart Controller. Which configuration accomplishes this task?

vpn 0 interface eth1 ip address 199.1.1.1/28 tunnel-interface allow-service sshd allow-service netconf no shutdown vpn 512 interface eth1 ip address 199.1.1.1/28 tunnel-interface allow-service sshd allow-service netconf vpn 0 interface eth1 ip address 199.1.1.1/28 tunnel-interface allow-service sshd allow-service ntp vpn 512 interface eth1 ip address 199.1.1.1/28 D. tunnel-interface allow-service netconf no allow-service ntp no allow-service stun

- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: A

QUESTION NO: 14

A customer has MPLS and Internet as the TLOC colors. An engineer must configure controllers with the Internet and not with MPLS. Which configuration achieve this requirement on vManage?

- A. vpn 0 interface eth1 ip address 10.50.0.1/24 tunnel-interface color default
- B. vpn 0
 interface eth1
 ip address 10.50.0.1/24
 tunnel-interface
 color biz-internet
- C. vpn 0
 interface eth1
 ip address 10.50.0.1/24
 tunnel-interface
 color public-internet
- D. vpn 0 interface eth1 ip address 10.50.0.1/24 tunnel-interface color mpls
- A. Option A
- B. Option B
- C. Option C
- D. Option D

ANSWER: A

QUESTION NO: 15

Which two hardware platforms support Cisco IOS XE SD-WAN images? (Choose two.)

- A. ISR4000 series
- B. ISR9300 series
- C. vEdge-1000 series
- D. ASR9000 series

E. ASR1000 series

1A	٧S	3V	۷	Е	R	:	Α	Ε
----	----	----	---	---	---	---	---	---

Explanation:

Reference: https://www.cisco.com/c/en/us/solutions/collateral/enterprise-networks/sd-wan/white_paper-c11-741071.html