

DUMPSQUEEN

VPLEX Specialist Exam for Implementation Engineers

EMC E20-260

Version Demo

Total Demo Questions: 15

Total Premium Questions: 210

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

When creating logging and metadata volumes, which LUN requirement applies to both volumes?

- A. Array LUNs must be zeroed-out.
- B. Array LUNs must be RAID 0
- C. Array LUNs must be thin.
- D. Array LUNs must be RAID 1

ANSWER: A

QUESTION NO: 2

A customer is moving some VMAX devices under a VPLEX Local and is using PowerPath as multipath software.

What is the SCSI product ID assigned to VPLEX volumes?

- A. Invista
- B. VPLEX
- C. PowerPath
- D. VMAX

ANSWER: A

QUESTION NO: 3

You are using VPLEX Unisphere to perform management functions in your environment. You are tasked with creating several volume migrations to a new storage array.

What tab should you use to perform this migration?

- A. Provision Storage
- B. Mobility Central
- C. System Status
- D. Performance Dashboard

ANSWER: B

QUESTION NO: 4

Refer to the exhibit.

```
C:\>powermt display dev=harddisk4
Pseudo name=harddisk4
----- ID=FNM00121800313
Logical device ID=6000144000000010E00C2ECB3C5914FB
state=alive; policy= -----; priority=0; queued-IOs=1
-----
----- Host ----- - Stor - -- I/O Path - -- Stats ---
### HW Path I/O Paths Interf. Mode State Q-IOs Errors
-----
 2 port2\path0\tgt1\lun0 c2t1d0 01 active alive 1 1
 2 port2\path0\tgt2\lun0 c2t2d0 04 active alive 0 0
 3 port3\path0\tgt0\lun0 c3t0d0 00 active alive 0 1
 3 port3\path0\tgt1\lun0 c3t1d0 05 active alive 0 0
```

A customer is moving some VMAX devices under a VPLEX Local and is using PowerPath as multipath software. What is the preferred PowerPath load balancing policy assigned to VPLEX volumes?

- A. Fixed
- B. Adaptive
- C. Round Robin
- D. SymOpt

ANSWER: B

QUESTION NO: 5

Which type of statistics are used to track latencies, determine median, mode, percentiles, minimums and maximums?

- A. Buckets
- B. Counters
- C. Readings
- D. Monitors

ANSWER: A

QUESTION NO: 6

In the distributed cache architecture, how much local cache does a VS2 director have?

- A. 36GB
- B. 64GB
- C. 32GB
- D. 72GB

ANSWER: C

QUESTION NO: 7

What information is required to configure ESRS for VPLEX?

- A.** VPLEX model type
Top Level Assembly
Site ID
IP address of the Management Server public port
- B.** Top Level Assembly
Site ID
IP address of the Management Server public port
VPLEX Configuration (1, 2 or 4 Engines)
- C.** VPLEX model type
Top Level Assembly
Primary customer contact
IP address of the Management Server public port
- D.** VPLEX model type
Site ID
IP address of the Management Server public port
Primary Customer contact

ANSWER: A

QUESTION NO: 8

What can you use to generate a list of VPLEX fabric initiator and target identifiers?

- A. WWN Utility
- B. Procedure Generator
- C. Powerlink
- D. Command Line

ANSWER: A

QUESTION NO: 9

What is the total number of available engines in the smallest VPLEX Metro configuration?

- A. 2
- B. 1
- C. 8
- D. 4

ANSWER: A

QUESTION NO: 10

How much distributed storage can be managed by a 20 GB logging volume?

- A. Up to 960 TB
- B. Up to 320 TB
- C. Up to 640 TB
- D. Up to 1.2 PB

ANSWER: C

QUESTION NO: 11

Refer to the exhibit.

```
VPlexcli:/engines/engine-1-2/directors/director-1-2-A/hardware/ports/A1-FC01> ll
Name                               Value
-----
address                             0x500014xxxxxxxx11
current-speed                         8Gbits/s
enabled                              true
max-speed                             8Gbits/s
node-wwn                             0x500014xxxxxxxxd9
operational-status                   ok
port-status                           up
port-wwn                             0x500014xxxxxxxx11
protocols                             [fc]
role                                  back-end
target-port                           -
topology                              loop
```

You are implementing a VPLEX Metro configuration, and some BE ports are not logged into the fabric.

Which VPLEX command should be performed?

- A. set topology p2p
- B. set enabled=true
- C. set topology loop
- D. set port speed

ANSWER: A

QUESTION NO: 12

A new VPLEX cluster has been configured. However, you are unable to register any host initiators. After verifying that the host has been properly zoned to the VPLEX cluster, you still cannot register them. What is a possible cause?

- A. Front end ports have not been enabled.
- B. Back-end ports have not been enabled.
- C. Back-end arrays have not presented any LUNs.
- D. Storage View for host has not been created.

ANSWER: C

QUESTION NO: 13


You have added a new storage array into VPLEX, but it does not see it. Which VPLEX command will display the new storage array?

- A. vplexcli:/clusters/cluster-/storage-elements/storage-arrays/array re-discover
- B. vplexcli:/array claim -s
- C. vplexcli:/clusters/cluster-//storage-elements/storage-arrays>array used-by-array
- D. vplexcli:/connectivity validate-be

ANSWER: A

QUESTION NO: 14

Refer to the exhibit.




A customer wants to implement a VPLEX Metro High Availability Cross Connect implementation between their two campus sites. What round-trip latency time requirement must be met between Site A and Site B?

- A. < 3 ms
- B. < 5 ms
- C. < 1 ms
- D. < 10 ms

ANSWER: C

QUESTION NO: 15

Refer to the exhibit.



The customer has not followed EMC best practices when cabling their VS2 VPLEX engine. What action would you recommend to fix this issue?

- A. Swap ports 00 with ports 01 of both director A and director B.
- B. Swap port 02 with port 03 of both director A and director B.
- C. Add two more additional fabrics and place each director in its own fabric.
- D. Separate all FE and BE ports into their own fabric.

ANSWER: A