

DUMPSQUEEN

Backup Recovery - Avamar Specialist Exam for Storage Administrators

EMC E20-598

Version Demo

Total Demo Questions: 15

Total Premium Questions: 237

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

You are configuring backups for Desktop/Laptop clients. According to best practices, what should you do to ensure that all Windows clients will have successful backups?

- A. Create a prescript that will initiate a VSS snapshot of the client
- B. Enable overtime so that backups can start outside their normal time
- C. Use the #USERDOCS# flag when creating the dataset
- D. Create a separate dataset and group for clients with Windows XP or earlier

ANSWER: C

Explanation:

Best practices for creating a dataset

- Create a backup dataset that specifies the files and folders for the backup.
- Exclude certain file types from desktop and laptop backups.
- If practicable, minimize the number of entries you define in exclude and include lists.
- In an environment that contains both Windows XP and Windows Vista or Windows 7 clients, add the `--x18=256` option to the dataset to prevent the "Path not found" error.

Table 15 on page 71 lists folders to include in a Desktop/Laptop dataset:

Table 15 Desktop/Laptop file types to include in a dataset

OS	Tab	Files and folders
Windows	Source Data	<pre>#USERDOCS#*\Desktop #USERDOCS#*\Documents #USERDOCS#*\My Documents #USERDOCS#*\Favorites</pre> <p>Notice: A change in the default location of the user directories was made between the Windows XP release, and the Windows Vista and Windows 7 releases. To handle this change, the Windows Desktop/Laptop plug-in uses #USERDOCS# as a variable that translates to the default location based on the specific Windows operating system.</p>
Mac	Source Data	<pre>/Users /Users/*/Desktop /Users/*/Documents /Users/*/Library/Safari</pre>

QUESTION NO: 2

Which type of EMC Avamar Gen4S node supports SAS drives?

- A. Accelerator node
- B. Business Edition node
- C. Media access node
- D. Storage node

ANSWER: A

QUESTION NO: 3

A node has failed on a multi-node EMC Avamar grid and is offline. The customer insists on running backups while the replacement is occurring.

What can you tell the customer about the impact of running backups during a node replacement procedure?

- A. Replacement procedure will take significantly longer with backups running
- B. Replacement procedure will be unaffected by running backups
- C. Replacement procedure cannot continue while backups are running
- D. Replacement procedure will take less time with backups running

ANSWER: A

QUESTION NO: 4

Based on the configuration represented in the exhibit, which type(s) of EMC Avamar replication can be used?



- A. Normal
- B. Full copy

- C. Root-to-root
- D. Normal and root-to-root

ANSWER: A

QUESTION NO: 5

A backup administrator is performing a disaster recovery for a Windows Server 2008 system. However, the Avamar Disaster Recovery Wizard is unable to perform the recovery.

What is a possible reason for this?

- A. Windows 2008 OS software has not been installed on the replacement hardware
- B. The Avamar Disaster Recovery Wizard does not support Windows 2008
- C. A backup using the Windows VSS plug-in and the full file system was not performed
- D. A backup using the Avamar Server Restore Option was not performed

ANSWER: B

Explanation:

While performing the backup of system state using Windows VSS plugin choose the option "Create Disaster Recovery Backup", this option will allow you to perform restore of the system using "Avamar disaster Recovery Wizard"

<https://community.emc.com/thread/114519>

QUESTION NO: 6

Which tool is used to move a client to a new domain in EMC Avamar 6.0?

- A. Client Manager
- B. Activation Manager
- C. Enterprise Manager
- D. Installation Manager

ANSWER: A

Explanation:

Clients page

Avamar Client Manager's **Clients** page provides information and tools for working with Avamar clients.

From the **Clients** page you can:

- ◆ Select the computers in your enterprise's domain and add them as Avamar clients
- ◆ View detailed information about individual clients
- ◆ Move, retire, and delete clients
- ◆ Change a client's group associations
- ◆ Upgrade the Avamar software on the client

To navigate between the sections of the Clients page, select from the choices in the left-side menu.

QUESTION NO: 7

What happens when files fail to find a match in the file cache during a backup of an EMC Avamar client computer?

- A. An "is present" call to the Avamar server
- B. Fewer chunks are compressed
- C. More files are processed for backup
- D. Increased memory swapping

ANSWER: C

QUESTION NO: 8

Your readiness checks show that a customer's Gen4 Avamar server has entered a read-only status. To avoid data loss, which recommended state should the Avamar server be in before you can continue the "Add Node" procedure?

- A. Known good controlled state
- B. Read-only state
- C. Steady state
- D. Suspended state

ANSWER: A

QUESTION NO: 9

Which RAID level is used in an EMC Avamar 7.8 TB single-node server?

- A. 1
- B. 5
- C. 6
- D. 10

ANSWER: A

QUESTION NO: 10

At which percentage of user capacity are new backups suspended in an EMC Avamar environment?

- A. 85
- B. 95
- C. 96
- D. 100

ANSWER: B

Explanation:

Capacity Threshold Warnings:

80% of user capacity = warning, start planning for expansion or cleanup

95% user capacity is the health check warning, new backups are suspended

100% user capacity makes the Avamar read-only, can still restore from server

85% of OS capacity = Garbage collection stops running, utilization increases rapidly

90% OS capacity = HFS checks stop running

96% OS capacity = no more checkpoints

QUESTION NO: 11

Which EMC tool provides all the necessary steps, in the correct order, to implement an EMC Avamar server?

- A. Avamar Procedure Generator

- B. EMC Backup System Sizer
- C. TS-Kit Configuration Guide
- D. TS-Kit Test Plan

ANSWER: A

QUESTION NO: 12

A Microsoft Windows user is about to start an on-demand backup using avtar when the utility node fails on their multi-node EMC Avamar server.

What must be done to ensure the backup will run and complete successfully?

- A. The utility node must be replaced and the configuration restored prior to starting the backup
- B. The spare node must be converted to a utility node and the configuration restored to the utility node
- C. The client must be activated temporarily to the first storage node and then the backup can be run
- D. Nothing. Backup is performed from the client to the storage nodes directly

ANSWER: D

Explanation:

storage nodes. This process is depicted in the included picture above. Lastly, in a previous blog, I discussed the 2 different licensable options for Avamar and how the disks are comprised in each Storage Nodes type. These are depicted in the picture above as well as a breakdown of how the disks are structured.

Please stop back by later, I plan to talk about the NDMP Accelerator and it's role in the Avamar System.

QUESTION NO: 13

What are the requirements for the virtual processor(s) dedicated to EMC Avamar Virtual Edition at all times?

- A. One 2 GHz virtual processor
- B. One 4 GHz virtual processor
- C. Two 2 GHz virtual processors
- D. Two 3 GHz virtual processors

ANSWER: D

Explanation:

Table 3 Minimum requirements for AVE

	0.5 TB AVE	1 TB AVE	2TB AVE	4 TB AVE
Processors	Minimum two 2 GHz processors	Minimum two 2 GHz processors	Minimum two 2 GHz processors	Minimum four 2 GHz processors
Memory	6 GB	8 GB	16 GB	36 GB
Disk space	850 GB	1,600 GB	3,100 GB	6,100 GB
Network connection	1 GbE connection	1 GbE connection	1 GbE connection	1 GbE connection

QUESTION NO: 14

What is the maximum number and types of nodes for an EMC Avamar multi-node server?

- A. 7 storage, 1 utility, and 1 spare
- B. 15 storage, 1 utility, 1 accelerator, and 1 spare
- C. 16 storage, 1 utility, and 1 spare
- D. 18 storage, 1 utility, and 1 spare

ANSWER: C

Explanation:

CAPACITY

Avamar Data Store systems are available from as little as 1.3 TB up to 124 TB of deduplicated disk storage capacity. Specialized management, media access, and NDMP Accelerator Nodes round out the offering.

	Scalable Architecture (Up to 16 storage nodes)	Single-Node (Requires replication)
Usable licensed deduplicated disk storage capacity	11.7 to 124.4 TB	1.3 TB/2.6 TB/3.9 TB/7.8TB
Equivalent cumulative, traditional backup storage	Up to several PB	Up to several hundred TB

QUESTION NO: 15

An EMC Avamar customer needs to estimate how much time it will take to replicate 3 TB of Avamar Source server data to their target server, given root-to-root migration. Using iperf, it is determined that data will be transferred at 54 GB/hour between the two Avamar servers.

How many hours will it take to replicate to the target?

- A. 76
- B. 81
- C. 89
- D. 99

ANSWER: B