

DUMPSQUEEN

Professional VMware vSphere 7.x

VMware 2V0-21.20PSE

Version Demo

Total Demo Questions: 10

Total Premium Questions: 109

Buy Premium PDF

<https://dumpsqueen.com>

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

Which action is supported over a VMkernel vMotion TCP/IP stack? (Choose the best answer.)

- A. Hot migrations
- B. Fault tolerance protection
- C. Virtual machine cloning
- D. Snapshot creation

ANSWER: B

QUESTION NO: 2

What are two minimum disk requirements for a vSAN hybrid disk group configuration?

(Choose two.)

- A. At least one magnetic data disk
- B. At least one SATADOM device
- C. At least two magnetic data disks
- D. At least one flash device
- E. At least two flash devices

ANSWER: C D

Explanation:

Reference: https://www.vmware.com/resources/compatibility/vsan_profile.html

QUESTION NO: 3

An administrator wants to be able to send vCenter Server log files to a remote syslog server and analyze logs using vRealize Log Insight.

Which step must the administrator take to meet this requirement? (Choose the best answer.)

- A. Configure the vCenter Server logging options using the vSphere Client.

- B. Specify the remote syslog server name at deployment using the vCenter Server GUI Installer.
- C. Specify the vRealize Log Insight system name using the vSphere Client.
- D. Configure log file forwarding using the vCenter Server Management Interface.

ANSWER: D

Explanation:

: <https://docs.vmware.com/en/VMwarevSphere/7.0/com.vmware.vsphere.vcenter.configuration.doc/GUID-9633A961-A5C3-4658B099->

[8B1E0512DC21.html?hWord=N4lghgNiBclG4GECmA7ALkgTgAgMpbI2wgHsBzbAMwEsI kBnEAXyA](https://docs.vmware.com/en/VMwarevSphere/7.0/com.vmware.vsphere.vcenter.configuration.doc/GUID-9633A961-A5C3-4658B099-8B1E0512DC21.html?hWord=N4lghgNiBclG4GECmA7ALkgTgAgMpbI2wgHsBzbAMwEsI kBnEAXyA)

QUESTION NO: 4

Which two storage technologies can an administrator use to deploy the Virtual Machine File System (VMFS)? (Choose two.)

- A. Fibre Channel storage
- B. vSAN storage
- C. Virtual Volumes storage
- D. NFS storage
- E. iSCSI storage

ANSWER: A E

Explanation:

Reference:

<https://www.vmware.com/content/dam/digitalmarketing/vmware/en/pdf/techpaper/vmwarevmfs-tech-overview-white-paper.pdf>

VMFS can be deployed on three kinds of SCSI-based storage devices:

- Direct-attached storage
- Fibre Channel storage
- iSCSI storage

QUESTION NO: 5

An administrator is asked to deploy a virtual machine (VM) that can sniff packets for the Security team.

Which setting must be set to “accept” on the VM’s port group? (Choose the best answer.)

- A. Promiscuous mode
- B. Forged transmits
- C. MAC address changes
- D. Traffic shaping

ANSWER: A

Explanation:

Reference: <https://blog.packet-foo.com/2013/04/capturing-packets-of-vmwaremachines/comment-page-1/>

QUESTION NO: 6

What is a requirement of Storage I/O Control? (Choose the best answer.)

- A. Storage connected through Fibre Channel
- B. Management by a single vCenter Server
- C. Datastores with multiple extents
- D. Automated storage tiering capabilities

ANSWER: B

Explanation:

Reference:

<https://docs.vmware.com/en/VMware-vSphere/7.0/com.vmware.vsphere.resmgmt.doc/GUID-37CC0E44-7BC7-479C-81DC-FFFC21C1C4E3.html>

QUESTION NO: 7

Which two performance tools can be used to monitor virtual machines outside the guest operating system? (Choose two.)

- A. vCenter Server performance charts
- B. Task Manager
- C. top
- D. esxtop
- E. Perfmon

ANSWER: A E

Explanation:

Reference: <https://docs.vmware.com/en/VMware->

[vSphere/6.5/com.vmware.vsphere.monitoring.doc/GUID- 7F81E75C-39AA-4EF5-A2C2-F82C518AC459.html](https://docs.vmware.com/en/VMware-vSphere/6.5/com.vmware.vsphere.monitoring.doc/GUID-7F81E75C-39AA-4EF5-A2C2-F82C518AC459.html)

QUESTION NO: 8

Which two statements are true regarding the use of firmware update packages in vSphere Lifecycle Manager? (Choose two.)

- A. A hardware support manager must be registered as a vCenter Server extension.
- B. The firmware and drivers add-on are distributed through the official VMware online depot.
- C. The firmware and drivers add-on can be used on clusters that are managed with baselines.
- D. The firmware and drivers add-on can add or remove components from the ESXi base image.
- E. The firmware and drivers add-on is provided by a third-party vendor.

ANSWER: A D

Explanation:

Reference:

[https://docs.vmware.com/en/VMware-vSphere/7.0/com.vmware.vsphere-lifecyclemanager.doc/GUID- 34AF5B19-FC80-4915-8358-D5FCC8A8E69E.html](https://docs.vmware.com/en/VMware-vSphere/7.0/com.vmware.vsphere-lifecyclemanager.doc/GUID-34AF5B19-FC80-4915-8358-D5FCC8A8E69E.html)

QUESTION NO: 9

An administrator is configuring ESXi host behavior before and during the remediation process.

Which remediation setting is supported only on select hardware platforms? (Choose the best answer.)

- A. VM migration
- B. HA admission control
- C. Maintenance mode failures
- D. Quick Boot

ANSWER: D

Explanation:

Reference: <https://docs.vmware.com/en/VMware-vSphere/7.0/com.vmware.vsphere.lifecycle-manager.doc/GUID-472964C3-70F3-4B83-8B1E-6C7CB4906DF8.html>

QUESTION NO: 10

What are two pre-requisites for enabling ESXi secure boot? (Choose two.)

- A. External Key Management Service
- B. vCenter Server 7.0 or greater
- C. Trusted Platform Module version 2.0
- D. ESXi 7.0 or greater
- E. Unified Extensible Firmware Interface (UEFI)

ANSWER: A E

Explanation:

: <https://blogs.vmware.com/vsphere/2017/05/secure-boot-esxi-6-5-hypervisorassurance.html>