DUMPSQUEEN

Using HPE OneView

HP HPE2-T37

Version Demo

Total Demo Questions: 5

Total Premium Questions: 40

Buy Premium PDF

https://dumpsqueen.com

support@dumpsqueen.com

dumpsqueen.com

DUMPSQUEEN

QUESTION NO: 1

Which statement about a server profile for an Apollo system is true?

- A. Fibre Channel connections can be defined
- **B.** UEFI optimized is the only available boot mode
- C. Virtual WWNs and MAC addresses can be defined
- D. Enclosure Group Is automatically selected

ANSWER: C

QUESTION NO: 2

Which types of support dump can be created using HPE OneView? (Select two.)

- **A.** Enclosure group support dump
- B. Appliance support dump
- C. Firmware deployment support dump
- **D.** Logical enclosure support dump
- E. Maintenance console support dump

ANSWER: DE

QUESTION NO: 3

What is a network set?

- A. It is a collection of all internal networks defined for a specific type of traffic like vSAN or vMotion.
- **B.** It is a collection of untagged Ethernet networks that form a named group to simplify server profile creation.
- **C.** It is a collection of tagged Ethernet networks that form a named group to simplify server profile creation.
- **D.** It is a collection of all networks configured within HPE OneView regardless of network type.

DUMPSQUEEN

Α	N	SI	۸	/E	R:	C

QUESTION NO: 4

Which parameters can be defined in a server profile template for HPE Synergy Compute Modules? (Select two.)

- A. partition layout for servers running Linux.
- B. IL0 IPv4 or IPv6 address.
- C. local storage and BIOS settings.
- D. NIC teaming setup at OS level.
- **E.** network and storage connectivity.

ANSWER: C E

QUESTION NO: 5

Refer to the exhibit.



A customer complains that firmware compliance is empty. The customer confirmed that Synergy Service Pack is uploaded to the HPE OneView repository. How should you respond?

- A. The refresh procedure must be performed on each logical enclosure to refresh firmware.
- **B.** All of the components are up to date and compliant with firmware baseline.
- **C.** The firmware repository service must be restarted using maintenance connection.

DUMPSQUEEN						
D. The firmware repository is not defined within firmware compliance report.						
ANSWER: C						