DUMPSQUEEN

Enterprise Routing and Switching - Specialist (JNCIS-ENT)

Juniper JN0-349

Version Demo

Total Demo Questions: 10

Total Premium Questions: 110

Buy Premium PDF

https://dumpsqueen.com

support@dumpsqueen.com

dumpsqueen.com

QUESTION NO: 1

Which two statements are true about GRE tunnels on Junos devices? (Choose two.)

A. Only one GRE tunnel can be included for each logical unit.

B. Multiple GRE tunnels can be included for each logical unit.

C. GRE interfaces can include multiple logical units.

D. GRE interfaces can include only a single logical unit.

ANSWER: A C

QUESTION NO: 2

Click the Exhibit button.

```
[edit protocols bgp]
user@router# show
import add-community;
export next-hop-self;
group ISPs {
    type external;
    import local-pref;
    export adv-aggregate;
    neighbor 172.30.1.1 {
        peer-as 65100;
    }
    neighbor 172.30.2.1 {
        export adv-custom;
        peer-as 65200;
    }
}
group Internal-Peers {
    type internal;
    neighbor 192.168.110.10;
    neighbor 192.168.110.20;
}
```

Which statement is true about the configuration shown in the exhibit?

A. Only the next-hop-self export policy will be evaluated when routes are sent to neighbor 172.30.1.1.

B. Both the adv-aggregate and adv-custom export policies will be evaluated when routes are sent to neighbor 172.30.2.1.

C. Both the adv-aggregate and next-hop-self export policies will be evaluated when routes are sent to neighbor 172.30.1.1.

D. Only the adv-custom export policy will be evaluated when routes are sent to neighbor 172.30.2.1.

ANSWER: D

QUESTION NO: 3

Which three statements describe what happens when processing a frame for a switched packet? (Choose three.)

A. The ingress PFE performs the MAC address lookup.

B. The frame enters the ingress port and is forwarded out all ports.

C. The frame enters the ingress port and is processed by the ingress PFE.

D. The ingress PFE sends the header information to the Routing Engine.

E. The egress PFE forwards the packet out the egress port towards the destination.

ANSWER: A C E

QUESTION NO: 4

What are three reasons a router would send out an IS-IS link-state PDU? (Choose three.)

A. A new external route is imported from BGP.

B. The router's link to a neighbor goes down.

C. A new neighbor exists on the link.

D. The cost of a link to an existing neighbor has changed.

E. IS-IS sends link-state PDUs at random intervals.

ANSWER: B C D

QUESTION NO: 5

Click the Exhibit button.

```
{master:0}
user@switch> show spanning-tree bridge
STP bridge parameters
Context ID                                  : 0
Enabled protocol                            : RSTP
    Root ID                                 : 8192.50:c5:8d:ae:db:41
    Root cost                               : 40000
    Root port                               : ge-0/0/14.0
    Hello time                              : 2 seconds
    Maximum age                             : 40 seconds
    Forward delay                           : 30 seconds
    Message age                             : 4
    Number of topology changes              : 1
    Time since last topology changes        : 64 seconds
    Topology change initiator               : ge-0/0/14.0
    Topology change last recvd. from        : 2c:6b:f5:31:06:0e
    Local parameters
        Bridge ID                           : 32768.50:c5:8d:ae:bd:41
        Extended system ID                  : 0
        Internal instance ID                : 0
```

Referring to the exhibit, which statement is correct?

A. The device is the root bridge?

B. The spanning tree session has timed out.

C. The local bridge priority is set to 8k.

D. The bridge priority on the root device is set to 8k.

ANSWER: D

QUESTION NO: 6

What are three valid BGP message types? (Choose three.)

A. refresh

B. hello

C. database descriptor

D. keepalive

E. update

QUESTION NO: 7

Click the Exhibit button.

```
[edit routing-options]
user@router# show  | display inheritance no-comments
static {
    defaults {
        preference 20;
    }
    route 0.0.0.0/0 {
        next-hop 172.18.1.1;
        preference 5;
    }
    route 192.168.1.2/32 next-hop 172.20.111.10;
    route 192.168.2.0/30 next-hop [ 172.20.66.2 172.20.77.2 ];
    route 172.20.112.0/24 next-hop [ 172.20.66.2 172.20.77.2 ];
}
```

Which two statements about the configuration shown in the exhibit are correct? (Choose two.)

A. Two next-hop interfaces should appear in the routing table for the 172.20.112.0/24 prefix.

B. Multiple equal-cost next hops are installed in the forwarding table for the 192.168.2.0/30 prefix.

C. The route preference is the same for each static route.

D. Only the selected next-hop interface should appear in the forwarding table for the 172.20.112.0/24 prefix.

ANSWER: A D

QUESTION NO: 8

By default, how long will a learned MAC address be retained in the bridge table on an EX Series switch?

A. 600 seconds

B. 3600 seconds

C. 300 seconds

D. 1800 seconds

QUESTION NO: 9

Exhibit:

```
user@host> show log messages | match 12ald | last 1
Apr 13 17:59:30 host 12ald[1229]: L2ALD_MAC_LIMIT_REACHED_IF: Limit
on learned MAC addresses reached for ge-
0/0/23.0; current count is 2
user@host> show configuration switch-options interface ge-0/0/23.0
interface-mac-limit {
     2;
     packet-action drop-and-log;
}
user@host> show configuration vlans
default {
     vlan-id 1;
     13-interface irb.1;
     switch-options {
          interface-mac-limit {
               3;
          packet-action drop-and-log;
     }
   }
}
user@host> show configuration interfaces irb
unit 1{
     family inet {
          address 172.25.11.10/24;
     }
}
```

You have an ESXi host that is connected to ge-0/0/23 on a Juniper EX Series switch. You added a new VM that will also use the same ge-0/0/23 interface. Unfortunately, the new VM is not able to reach external devices.

Referring to the exhibit, which command would solve this problem?

A. set vlans default switch-options interface-mac-limit 4

B. set vlans default switch-options interface-mac-limit 5

C. set switch-options interface ge-0/0/23.0 interface-mac-limit 3

D. clear ethernet-switching recovery-timeout interface ge-0/0/23.0

ANSWER: C

QUESTION NO: 10

Click the Exhibit button.


```
{master:0}[edit protocols rstp]
user@Switch-1# show
bridge-priority 4k;
interface ge-0/0/8.0 {
    cost 1;
}
interface all {
    priority 128;
    cost 200000;
}
```

```
{master:0}[edit protocols rstp]
user@Switch-2# show
bridge-priority 8k;
interface ge-0/0/10.0 {
    cost 1;
}
interface all {
    priority 16;
    cost 20000;
}
```

```
{master:0}[edit protocols rstp]
user@Switch-3# show
bridge-priority 32k;
interface all {
    priority 16;
    cost 2000;
}
```

```
{master:0}[edit protocols rstp]
user@Switch-4# show
bridge-priority 36k;
interface all {
    priority 128;
    cost 20000;
}
```

Switch-1   ge-0/0/1.0   Switch-2

ge-0/0/8.0   ge-0/0/10.0   ge-0/0/8.0   ge-0/0/9.0

ge-0/0/12.0

Switch-3   ge-0/0/13.0   Switch-4

Referring to the exhibit, which port will be selected as the RSTP root port on Switch-4?

A. ge-0/0/13.0

B. ge-0/0/8.0

C. ge-0/0/9.0

D. ge-0/0/12.0

ANSWER: D