DUMPSQUEEN

Linux Foundation Certified System Administrator

Linux Foundation LFCS

Version Demo

Total Demo Questions: 15

Total Premium Questions: 260

Buy Premium PDF

dumpsqueen.com

QUESTION NO: 1

Which of the following keywords can be used in the file /etc/nsswitch.conf to specify a source for host name lookups? (Choose TWO correct answers.)

A. resolv

B. dns

C. remote

D. files

E. hosts

ANSWER: B D

QUESTION NO: 2

What does the command mount -a do?

A. It mounts all available filesystems onto the current directory.

B. It shows all mounted filesystems.

C. It mounts all user mountable filesystems for the current user.

D. It mounts all filesystems listed in /etc/fstab which have the option auto set.

E. It mounts all filesystems listed in /etc/fstab which have the option noauto set.

ANSWER: D

QUESTION NO: 3

What of the following can be done by the command ifconfig? (Choose TWO correct answers.)

A. Set a network interface active or inactive.

B. Specify the kernel module to be used with a network interface.

C. Allow regular users to change the network configuration of a network interface.

D. Change the netmask used on a network interface.

E. Specify which network services are available on a network interface.

ANSWER: A D

QUESTION NO: 4

After modifying GNU GRUB's configuration file, which command must be run for the changes to take effect?

A. kill -HUP $(pidof grub)

B. grub-install

C. grub

D. No action is required

ANSWER: D

QUESTION NO: 5

What is the purpose of the Bash built-in export command?

A. It allows disks to be mounted remotely.

B. It runs a command as a process in a subshell.

C. It makes the command history available to subshells.

D. It sets up environment variables for applications.

E. It shares NFS partitions for use by other systems on the network.

ANSWER: D

QUESTION NO: 6

What does the command mount -a do?

A. It ensures that all file systems listed with the option noauto in /etc/fstab are mounted.

B. It shows all mounted file systems that have been automatically mounted.

C. It opens an editor with root privileges and loads /etc/fstab for editing.

D. It ensures that all file systems listed with the option auto in /etc/fstab are mounted.

E. It ensures that all file systems listed in /etc/fstab are mounted regardless of their options.

ANSWER: D

QUESTION NO: 7 - (FILL BLANK)

Which command is used to sync the hardware clock to the system clock? (Specify ONLY the command without any path or parameters.)

ANSWER: hwclock, /sbin/hwclock, /usr/sbin/hwclock

QUESTION NO: 8 - (FILL BLANK)

Which command will disable swapping on a device? (Specify ONLY the command without any path or parameters.)

ANSWER: swapoff, /sbin/swapoff

QUESTION NO: 9

What is true regarding the file ~/.forward?

A. As it is owned by the MTA and not writable by the user, it must be edited using the editaliases command.

B. After editing ~/.forward the user must run newaliases to make the mail server aware of the changes.

C. Using ~/.forward, root may configure any email address whereas all other users may configure only their own addresses.

D. When configured correctly, ~/.forward can be used to forward each incoming mail to more than one other recipient.

ANSWER: D

QUESTION NO: 10

The script, script.sh, consists of the following lines:

#!/bin/bash

echo $2 $1

Which output will appear if the command, ./script.sh test1 test2, is entered?

A. test1 test2

B. test2 test1

C. script.sh test2

D. script.sh test1

E. test1 script.sh

ANSWER: B

QUESTION NO: 11

After moving data to a new filesystem, how can the former path of the data be kept intact in order to avoid reconfiguration of existing applications? (Choose TWO correct answers.)

A. By creating an ACL redirection from the old to the new path of the data.

B. By creating a hard link from the old to the new path of the data.

C. By creating a symbolic link from the old to the new path of the data.

D. By running the command touch on the old path.

E. By mounting the new filesystem on the original path of the data.

ANSWER: C E

QUESTION NO: 12 - (FILL BLANK)

With IPv6, how many bits have been used for the interface identifier of an unicast address? (Specify the number using digits only.)

ANSWER: 64

QUESTION NO: 13 - (FILL BLANK)

The system's timezone may be set by linking /etc/localtime to an appropriate file in which directory? (Provide the full path to the directory, without any country information)

ANSWER: /usr/share/zoneinfo/

QUESTION NO: 14

Which of the following commands can be used to display the inode number of a given file?

A. inode

B. ls

C. ln

D. cp

ANSWER: B

QUESTION NO: 15

What is the maximum niceness value that a regular user can assign to a process with the nice command when executing a new process?

A. 9

B. 19

C. 49

D. 99

ANSWER: B